

MONITORING

We use 5 wireless in-ear monitors. Shure PSM900, L6E, 656-692MHz

ELECTRICITY

Our stage rack needs 16A power. Our rack has a distribution center from which we take power

CABLES

We use our own stagebox, which connects to our stage rack, and the power also runs on the side of these.

L/R

L/R feed preferably from the stage rack. It can also be done from the front if necessary.

FOH

We have a Midas M32R mixer and a stage box in the rack. We need a CAT connection between FOH and STAGE RACK. Table or case under the mixer and electricity

BÄCKLINE

We bring all the instruments and amplifiers with us. We use our own microphones and bring our own mic stands. The drums are placed on a raiser if possible.

TECHNICIAN:

Valtteri Seitsalo

+358 44 334 8344

komiatcrew@gmail.com

I / O patch

СН	Source / Instrument	+48v Phantom		Mic	Stand	OUTPUT	
1	BD	+48v		SHURE BETA91A	-	1-2	IEM DRUMS
2	SNARE			SHURE SM57	Clip	3-4	IEM GTR
3	SNARE B.	+48v		BEYERDYNAMIC OPUS 87	Clip	5-6	IEM ACC
4	RACK TOM	+48v		BEYERDYNAMIC OPUS 87	Clip	7-8	IEM LEAD
5	FLOOR TOM	+48v		BEYERDYNAMIC OPUS 87	Clip	9-10	IEM BASS
6	OH L (RIDE)	+48v		RODE NT5	Clip / underhead	11-12	
7	OH R (HH)	+48v		RODE NT5	Clip / underhead	13-14	
8	BASS			LINE OUT	-	15-16	L/R
9	GTR amp 1			SENNHEISER E906	Short Boom		
10	GTR amp 2			SHURE SM57	Short Boom		
11	AC. GTR	+48v		LINE OUT FROM PEDALS	-		
12	ACCORDION	+48v	DI		-		
13	VOC GTR			SE V7	ROUND BASE SRAIGHT		
14	VOC BASS			SHURE SM58	ROUND BASE SRAIGHT		
15	VOC LEAD			SE V7	ROUND BASE SRAIGHT		
16	AMBIENCE L	+48v		RODE NT5			
17	AMBIENCE R	+48v		RODE NT5			
18	TALCKBACK						